

RECORD CLC16 SERIES

HEAVY DUTY WRAPOVER STACKER

TRAVEL SPEED
UNLADEN **5km/h**

MAX LIFTING HEIGHT
UP TO **3300mm**

MAX CAPACITY
1600kg

PUMP MOTOR
3kW



	Model		CLC1614H	CLC1625H	CLC1633H
Feature	Type		Wrap over		
	Mast Type		2-Stage STD		
	Load Capacity	kg	1600		
	Load Center	mm	600		
	Wheel Base	mm	1325		
	Operating Type		Walkie / Stand On		
Wheels	Wheels Type		PU		
	Wheel Quantity Driving/Balance/Bearing		1/2/4		
Dimension	Standard Lift Height	mm	1400	2500	3300
	Lowered Fork Height	mm	90		
	Fork Size (length/width/thickness)	mm	1150(1220)/185/55		
	Overall Length	mm	2050/2470		
	Overall Width	mm	856		
	Max Extend Height	mm	1900	3000	3800
	Mast Lowered Height	mm	1185	1765	2135
	Min. Turning Radius	mm	1580/1990		
	Min. Aisle Width for Pallets 800 x 1200	mm	2180/2580		
	Min. Aisle Width for Pallets 1000 x 1200	mm	2210/2600		
	Min. Ground Clearance	mm	30		
Performance	Travel Speed (Laden/Unladen)	km/h	5/5		
	Lift Speed (Laden/Unladen)	mm/s	130/180		
	Lowering Speed (Laden/Unladen)	mm/s	100/200		
	Gradeability (Laden/Unladen)	%	5/7		
Electrical	Drive Motor/Lift Motor/Steering Motor	KW	AC1.5/DC3/DC0.15		
	Battery Voltage	V	24		
	Battery Capacity	Ah	280		
	Brake		Electromagnetic / Regenerative		
	Controller		CURTIS		
Weight	Battery Weight	kg	250		
	Service Weight with Battery	kg	1240		